

# ESTANCA CHROMAX



167lm/W LED



Superior a las estancas convencionales / Superior to conventional triproof / Supérieur aux étanches classiques

- La ESTANCA CHROMAX cuenta con un alto índice de reproducción cromática.
- Estanca diseñada con Tubos LED fabricados con PCB de aluminio para una mayor disipación.
- Extremos con sistema rotatorio para una perfecta orientación del haz luminoso.
- Difusor de Policarbonato para garantizar el máximo rendimiento.
- Protección UV contra el envejecimiento.
- Opción regulable.
- Accesorios (consultar): clips en acero para fijación directa a superficie (incluidos)(1), clips en acero para suspensión (incluidos)(2), clips de cierre en acero inox (opcional)(3).

- The ESTANCA CHROMAX has a high color rendering index.
- ESTANCA CHROMAX is designed with LED tubes made of aluminum PCB for greater dissipation.
- Polycarbonate diffuser to ensure maximum performance.
- Accessories (check with us): steel clips for direct surface fixing (included) (1), steel suspension clips (included) (2), steel clips (optional) (3).

- L'étanche CHROMAX a un haute indice de rendu des couleurs.
- Étanche designé avec tubes LED montés sur dissipateur d'aluminium.
- Angle d'ouverture variable grâce au capuchon pivotant.
- Protection UV contre le vieillissement.
- Diffuseur en polycarbonate pour garantir une performance maximum.
- Option dimmable.
- Accesorios (consulter les options): Clips en acier pour fixer sur le plafond (1) clips en acier pour suspension (2), clips de verrouillage en acier (3).

SUSTITUCIÓN / REPLACEMENT / REMPLACEMENT

Estanca FL		W LED
0.6m	18W	9W
2x0.6m	2x18W	18W
1.2m	36W	17W
2x1.2m	2x36W	34W
1.5m	58W	22W
2x1.5m	2x58W	44W



Clips fijación superficie en acero (incluido).  
Clips for direct surface fixing of steel (included).  
Clips pour fixer sur le plafond en acier (inclus).

1



Clips para suspensión en acero (incluido).  
Clips for suspension of steel (included).  
Clips pour suspension en acier (inclus).

2





Clips de cierre en acero inox (opcional).  
Closing clips of stainless steel (optional).  
Clips de verrouillage en acier inox (optionnel).

3



Tubo LED incluido.  
LED tube included.  
Tube LED inclus.

4



long.	Ref.	Temp.	Ra/IRC	W
1x0.6m	LD-1918009-860	6000 K	≥85	100-264V AC 9W
2x0.6m	LD-1918018-860	6000 K	≥85	100-264V AC 18W
1x1.2m	LD-1918017-860	6000 K	≥85	100-264V AC 17W
2x1.2m	LD-1918034-860	6000 K	≥85	100-264V AC 34W
1x1.5m	LD-1918022-860	6000 K	≥85	180-264V AC 22W
2x1.5m	LD-1918044-860	6000 K	≥85	180-264V AC 44W



\* Consultar / Consult / Consulter